

SERIES 112T

PUMP MATERIALS

Pump Body: Teflon hard coated aluminum
 Plunger: 304SS
 Seals: Proprietary Teflon blend
 Elastomers: Viton

SPECIFICATIONS

Flow: to 1.5 GPM
 Pressure: to 250 PSI
 Temperature: to 120°F
 RPM(max): 2400
 Inlet: 1/4 F NPT(2)
 Outlet: 1/4 F NPT(2)

Sprayer pump for applications up to 1.5 GPM, 250 PSI



PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80069	112T-075/M9	1.4	20	'20	5.3	8
		1.4	35	'15	6.8	8
		1.27	65	'10	7.5	8
		1.2	90	'08	8.8	8
		1.06	125	'06	10.8	8

PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80010	112T-075/M15	1.4	20	'20	4.5	10
		1.4	35	'15	6.0	10
		1.22	60	'10	7.0	10
		1.16	85	'08	8.0	10
		1.08	130	'06	10.0	10
		1.05	175	'05	13.0	10
		0.94	220	'04	14.5	10

PN	MODEL	GPM	PSI	NOZZLE	AMP	Weight (lbs.)
80019	112T-075/M17	1.55	25	'20	4.5	10
		1.5	40	'15	5.2	10
		1.41	80	'10	7.2	10
		1.33	110	'08	8.9	10
		1.2	160	'06	12.0	10
		1.12	200	'05	14.5	10
		1.03	250	'04	17.0	10